

PP- DAN-STRONG / POLYPROPYLENE POLYSTEEL 8 STRAND

Dia (mm)	Feet/Kg	MBL			Maximum Length- Mtr
		Kgf	Lbs	KN	
40	4.57	28000	61600	274.51	270
44	3.73	33750	74250	330.88	220
48	3.15	39500	86900	387.25	520
52	2.67	45750	100650	448.53	450
56	2.31	52000	114400	509.80	380
60	2.01	59500	130900	583.33	330
64	1.77	67550	148610	662.25	290
68	1.57	76000	167200	745.10	260
72	1.40	84500	185900	828.43	450
76	1.26	94000	206800	921.57	400
80	1.13	104000	228800	1019.61	350
84	1.03	114000	250800	1117.65	320
88	0.93	125000	275000	1225.49	300
92	0.85	136000	299200	1333.33	270
96	0.79	148000	325600	1450.98	250
100	0.72	159166	350165.2	1560.45	220
104	0.67	169500	372900	1661.76	220
*112	0.55	195600	430320	1917.65	*180
*116	0.52	207030	455466	2029.71	*170
*120	0.49	224600	494120	2201.96	*160

*112 MM available only in 180 mtrs Length. *116 MM available only in 170 mtrs Length. *120 MM available only in 160 mtrs Length

Note: The MBL should never be considered as the safe working load of Rope. For the method of calculating safe working load please refer factor of safety = Breaking force/6. Specifications subject to ± 5% variation.

*Manufactured in accordance with 'OCIMF' guidelines.