



MANUAL VIEW

Stock No.	Standard	Dimensions (mm)										load(ton)	Weight (kg)
		A	B	C	D	E	F	G	H	I	J		
006	5/8"×9"	661	401	228	276	33	19	13	201	147	33	1.6	1.6
009	3/4"×9"	698	432	228	285	38	24	16	216	154	41	2.4	2.5
012	7/8"×12"	891	542	305	371	45	28	19	271	198	48	3.3	3.7
016	1"×18"	1237	730	457	533	52	30	22	365	280	54	4.5	6.9
019	1-1/4"×18"	1316	796	457	536	71	44	28	398	286	66	6.9	11.2
023	1-1/2"×24"	1663	978	610	705	71	52	35	489	374	79	9.7	18.5
025	1-3/4"×24"	1660	1051	610	721	86	60	41	526	385	89	12.7	28.8
026	2"×24"	1766	1157	610	737	94	63	50	578	396	106	16.8	42.8
027	2-1/2"×24"	1853	1244	610	789	113	78	57	622	437	143	27.2	74.9
028	2-3/4"×24"	1898	1289	610	789	113	93	70	645	440	155	34.0	89.9

- Forged carbon steel - Normalizing
- Electric plated or Hot-Dip galvanized.
- Turnbuckle Jaw & Jaw meet the performance requirements of ASTM F 1145 Type 1, Grade 1, Class G.
- Proof load is 2.5 times the S.W.L. and the breaking load is 5.0 times the S.W.L.
- Forged jaw ends are fitted with bolts and nuts for 3/8"~5/8", and pins and cotter on 3/4" through 2-3/4" sizes.

