

Mooring Line Certificate

Demonstrates that the product has been manufactured, tested & documented following the guidelines in appendix B of the *Mooring Equipment Guidelines, Fourth Edition*.

Name & Address of Manufacturer : Kohinoor Ropes Pvt. Ltd. Selu-431 503 Dist. Parbhani, Maharashtra, India

Line Standard : Manufactured according to ISO 10572:2010 &
 Tested according to ISO 2307:2019

Line supply information

Ship design MBL	-	Certificate No.	KRP/23/04/42440029/01
NSBF	33.78 M Tons	Date	28-04-2023
Diameter	44 mm	Coil No.	01 to 40
Length	220 m		
Jacketed	No		
Splice type and design	Eye (Six Tucks)		
Material type and grade	Polypropylene		
Line design designation (product name)	PP TECHPLUS		
Line construction	8-Strand Braided		
Rotating	No		

Performance Indicators

Line Design Break Force (LDBF)	33.60 M Tons				
Line Linear Density (LLD)	990 gm/m				
Load Bearing Linear Density (LBLD)	990 gm/m				
	Measured		Maximum		
Line Tenacity (LT)	0.0339 M Tons / (gm/m)		0.0339 M Tons / (gm/m)		
	D/d Ratio:5		D/d Ratio:10		
Angled Break Force* (ABF) % Avg NSBF	203.08		217.87		
Angled Endurance* (AE) % Avg NSBF	68.05		67.64		
	-20° C	0° C	20° C	40° C	60° C
Temperature (T) % BF at 20° C	100.49	100.06	100.00	99.54	99.42
	80° C				
Axial Compression Resistance* (ACR)	129.11 % Avg NSBF				
	%LDBF:10	%LDBF:20	%LDBF:30	%LDBF:40	%LDBF:50
Average Immediate Strain* (e)	6.06	6.81	7.74	8.65	9.43

Line Description

8 Strand PP TECHPLUS Rope, Green / 2 Yellow Ty, With 1.8 mtr Eye-Splicing Wrapped With Canvas At Both Ends, UV Resistant



 A handwritten signature in blue ink.

QC Incharge