



HASÇELİK

HAS ÇELİK ve HALAT SANAYİ TİCARET A.Ş.

ÇELİK TEL VE HALAT FABRİKASI

Erciyes Mah. Hes Cad. No: 67 PK. 38210 Hacılar / KAYSERİ

Tel : 0352 442 16 40 (8 Hat) Faks : 0352 442 16 44

www.hascelik.com.tr • hascelik@hascelik.com.tr

MILL'S TEST CERTIFICATE



DATE : 02.01.2025

NO : 25000061
ORDERING COMPANY : KAPTAN ÇELİK HALAT SAN.TİC.A.Ş.

DIAMETER (mm) : 30,00
LAY : s/Z
LUBRICATION : A2
REEL NO : 1112985061

STANDARD : EN 12385-4

TENSILE STRENGTH (N/mm²) : 1960
LENGTH (M) : 1000

CONSTRUCTION : 6x36 WS IWRC
COATING : GALVANIZED

CHEMICAL ANALYSE OF WIRE ROD:

C %	Si %	Mn %	P max%	S max%
0,68 - 0,78	0,10-0,30	0,50-0,80	0,030	0,030

TEST RESULTS:

Number of wires	Diameter (mm)	Tensile Strength (N/mm ²)	Bend test (Number)	Torsion test (Number)	Zinc (gr/m ²)	Test on knotted wire (daN)
6	1,90	2052	12	29	122	
42	1,41	2050	14	33	109	
42	1,37	2055	15	40	104	
42	1,06	2063	25	33	91	
84	1,70	2040	16	42	108	
1	1,53	2035	21	30	110	
6	1,39	2049	14	42	98	
6	1,32	2061	15	36	99	
36	1,20	2028	17	42	93	

We hereby certify that the commodity is inspected according to EN 12385 and found good in all respects as stated above. You can use QR CODE for certificate verification

Minimum Breaking Load : 629 KN
Actual Breaking Load : 640 KN

Hatice VURAL
HASÇELİK GROUP
QUALITY AND ENVIRONMENT
MANAGER

TİCARET SİCİL NO : 14905
MİMARŞİNAN V.D. : 4580010964



DNV

TSE