



## Teklif No: 202512-0754

### Teklif Verilen

Şimşekler Genel Kumanyacılık ve Dış Tic. ve San. A.Ş.  
Kultur Mahallesi 240 Sk. No:1 Kat:3 D:7  
35800 Aliağa  
İZMİR / TÜRKİYE

### Talep Bilgileri

Talep Numarası: 202512-0754  
Tarih: 17 12 2025 11:38

| Sıra | Impa | Açıklama   | Birim | Miktar | Birim Fiyatı | Para Birimi | Remarks   | Teslimat Süresi | Toplam          |
|------|------|--|-------|--------|--------------|-------------|---|-----------------|-----------------|
| 1    | -    | 80,00 Meter galvanised steelwire rope **<br>2,00 - plain end Diameter: 12 mm; Lay:<br>Right hand regular lay; SWL: 5:1; Tensile<br>strength: 1770 n/mm <sup>2</sup> ; Construction:<br>6x37+fc; Breaking load: 75,1Kn  | PCE   | 2.00   | 113.00       | EUR         | 12 MM<br>6X36 WS<br>+ FC GALV<br>890 M<br>WIRE<br>ROPE -<br>BOTH<br>ENDS<br>PLAIN                           | 1               | 11288.70<br>TRY |
| 2    | -    | 40,00 Meter galvanised steelwire rope **<br>1,00 Piece Galvanised thimble mechanical<br>spliced 1,00 - plain end Diameter: 12 mm;<br>Lay: Right hand regular lay; SWL: 5:1;<br>Tensile strength: 1770 n/mm <sup>2</sup> ;<br>Construction: 6x37+fc; Breaking load:<br>75,1Kn             | PCE   | 2.00   | 60.00        | EUR         | 12 MM<br>6X36 WS<br>+ FC GALV<br>40 M WIRE<br>ROPE - 1<br>END<br>THIMBLE<br>MECH<br>SPliced                 | 1               | 5994.00<br>TRY  |
| 3    | -    | 59,00 Meter galvanised steelwire rope non-<br>rotating ** 2,00 Pieces welded end<br>Diameter: 08 mm; Lay: Right hand regular<br>lay; Tensile strength: 1960 n/mm <sup>2</sup> ; SWL:<br>5:1; Construction: 19x7; Breaking load: 43<br>Kn **4strand na**                                  | PCE   | 1.00   | 75.00        | EUR         | 8 MM<br>19X7<br>ROTATION<br>RESISTANT<br>GALV 59 M<br>WIRE<br>ROPE  | 1               | 3746.25<br>TRY  |
| 4    | -    | 60,00 Meter stainless steelwire rope AISI-<br>316 ** 2,00 - plain end Diameter: 04 mm;<br>Lay: Right hand regular lay; SWL: 5:1;<br>Construction: 7x19; Tensile strength: 1570<br>n/mm <sup>2</sup> ; Breaking load: 9,3 Kn  | PCE   | 1.00   | 30.00        | EUR         | 4 MM<br>7X19 AISI<br>316 SS 60<br>M WIRE<br>ROPE  | 1               | 1498.50<br>TRY  |
| 5    | -    | 61,00 Meter galvanised steelwire rope non-<br>rotating 1,00 Piece Galvanised thimble<br>mechanical spliced 1,00 Piece welded end<br>Diameter: 12 mm; Lay: Right hand regular<br>lay; Tensile strength: 1960 n/mm <sup>2</sup> ; SWL:<br>5:1; Construction: 19x7; Breaking load: 96<br>Kn | PCE   | 1.00   | 130.00       | EUR         | 12 MM<br>19X7<br>ROTATION<br>RESISTANT<br>GALV 61<br>MWIRE<br>ROPE - 1<br>END<br>THIMBLE<br>MECH<br>SPliced | 1               | 6493.50<br>TRY  |
| 6    | -    | 70,00 Meter galvanised steelwire rope non-<br>rotating ** 2,00 Pieces welded end<br>Diameter: 12 mm; Lay: Right hand regular<br>lay; Tensile strength: 1960 n/mm <sup>2</sup> ; SWL:<br>5:1; Construction: 19x7; Breaking load: 96<br>Kn   | PCE   | 1.00   | 150.00       | EUR         | 12 MM<br>19X7<br>ROTATION<br>RESISTANT<br>GALV 70 M<br>WIRE<br>ROPE   | 1               | 7492.50<br>TRY  |

|    |   |   |     |      |        |     |   |   |                 |
|----|---|---|-----|------|--------|-----|---|---|-----------------|
| 7  | - | 87,00 Meter galvanised steelwire rope **<br>2,00 - plain end Diameter: 14 mm; Lay:<br>Right hand regular lay; SWL: 5:1; Tensile<br>strength: 1770 n/mm <sup>2</sup> ; Construction:<br>6x37+fc; Breaking load: 102 Kn   | PCE | 1.00 | 155.00 | EUR | 14 MM<br>6X36 WS<br>+ FC GALV<br>87 M WIRE<br>ROPE  | 1 | 7742.25<br>TRY  |
| 8  | - | 64,00 Meter galvanised steelwire rope non-<br>rotating ** 1,00 Piece Galvanised thimble<br>mechanical spliced 1,00 Piece welded end<br>Diameter: 16 mm; Lay: Right hand regular<br>lay; Tensile strength: 1960 n/mm <sup>2</sup> ; SWL:<br>5:1; Construction: 19x7; Breaking load:<br>173 | PCE | 1.00 | 212.00 | EUR | 16 MM<br>19X7<br>ROTATION<br>RESISTANT<br>GALV 64<br>MWIRE<br>ROPE - 1<br>END<br>THIMBLE<br>MECH<br>SPliced | 1 | 10589.40<br>TRY |
| 9  | - | 59,00 Meter galvanised steelwire rope **<br>2,00 Pieces Aluminium ferrules 12 mm<br>according to DIN-3093A Diameter: 10 mm;<br>Lay: Right hand regular lay; SWL: 5:1;<br>Tensile strength: 1770 n/mm <sup>2</sup> ; Breaking<br>load: 52,2 Kn; Construction: 6x37+fc 2 x<br>stopper dia   | PCE | 2.00 | 70.00  | EUR | 10 MM<br>6X36 WS<br>+FC 59 M<br>WIRE<br>ROPE-<br>BOTH<br>ENDS<br>STOP                                       | 1 | 6993.00<br>TRY  |
| 10 | - | 49,00 Meter galvanised steelwire rope **<br>2,00 - plain end Diameter: 08 mm; Lay:<br>Right hand regular lay; Tensile strength:<br>1960 n/mm <sup>2</sup> ; SWL: 5:1; Construction:<br>6x36+IWRC; Breaking load: 44,7 Kn  | PCE | 1.00 | 60.00  | EUR | 8 MM<br>19X7<br>ROTATION<br>RESISTANT<br>GALV 49 M<br>WIRE<br>ROPE  | 1 | 2997.00<br>TRY  |

**Toplam: 64835.10 TRY**

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat cupidatat non proident, sunt in culpa qui officia deserunt mollit anim id est laborum.

Aliquam odit fugiat qui perferendis, asperiores hic dicta doloribus repudiandae magni sequi ea sapiente quia officii. Impedit culpa illum nam omnis eaque, beatae quis quos incidunt ullam porro similique nihil consectetur distinctio, ipsam quidem ea, ea tempora sint atque officii ducimus minima minus porro? Possimus nesciunt doloribus vel sapiente atque.

Expedita exercitationem quae laborum impedit fugit quod cumque dolorum enim? Voluptas nostrum dolores delectus quisquam veniam quas quos cumque, adipisci et amet veniam itaque sequi?